

As another telephone mounting angle varying apparatus, there is one wherewith a telephone main body 161 is set in a desired mounting angle by changing the position of an angle varying member 161b attached so that it turns freely to the telephone main body 161, as shown in Fig. 42 53.

Please amend the paragraph beginning at page 5, line 11, which starts with "In order to set the telephone" as follows:

In order to set the telephone main body 161 at a small mounting angle, the angle varying member 161 b is folded against the lower surface portion of the telephone main body 161, as shown in Fig. 42(a) 53(a).

*Km
5/16/06*
Please amend the paragraph beginning at page 5, line ¹⁴~~10~~, which starts with "In order to set a large" as follows:

In order to set a large mounting angle, on the other hand, the angle 15 varying member 161 b is separated from the lower surface portion of the telephone main body 161 and the other end thereof is made to come up against the mounting surface for the telephone set as shown in Fig. 42(b) 53(b).

Please amend the paragraph beginning at page 6, line 4, which start with "Even with mounting angle" as follows:

Even with mounting angle varying apparatuses wherewith a plurality of 5 mounting angles can be set, in order to set the mounting angle of the telephone main body 131, that must be done while visually verifying the engagement between the angle adjustment holes 131k1 to 13 1k4 and the engagement portion of the telephone base